



MAIN FEATURES

- Tri-amp 3 Way Active Point Source
- Coaxial Mid-High components
- Extended Low-end Response for VIO X315
- 137 dB max SPL
- 1400 W RMS Digipro G4 Amp Technology
- Neodymium Transducers
- Linear Phase FIR Filters
- Full-range SMPS with PFC
- Modular Slot for Network and Digital Audio Expansion Cards (RDNet card installed)
- System Test for Quick Transducers Diagnostics
- Flyable with accessories

DESCRIPTION

VIO X315, it is equipped with a single high performance 15inch neodymium woofer, capable of providing loud, precise, wide band performances, with no compromises. VIO X315 is a real full-range PA system, with an astounding wide frequency response, reaching as low as 37Hz.

In this model, the mid-hi coaxial transducer is placed behind a 90°x50° horn which has been designed with a slight tilt downwards (around 5°) to optimize the coverage in average venues.

ACCESSORIES



TC-VIOX310

Transport cover for X310



RC-X3

Raincover for VIO X310 amplifier

Speaker Type	3 Way Active Loudspeaker
Frequency Response [-10dB]	34 - 19.200 Hz
Frequency Response [-6dB]	37 - 18.000 Hz
Max SPL	137 dB
HF	1x 4", 4"- 2.5" v.c. Coaxial Neo
LF	1x 15", 4" v.c Neo
Directivity	90° x 50° - 5° tilted down [H x V]
Amplifier	1400 W RMS Class-D Digipro® G4
AD/DA Converter	24 bit/96 kHz
Limiter	Peak, RMS, Thermal
Processing	FIR Linear Phase Filters
Signal Input	1 x XLR balanced, 1 x RJ45 Link (RD-Net), 1x USB (Data Service)
Signal Output	1x XLR balanced, 1 x RJ45 Link (RD-Net)
Power Socket	1x PowerCON TRUE1 In 1x PowerCON TRUE1 Out
Controls	1x input Rotary Encoder (8x presets) 1x Ready LED 1x Mute/Prot LED 1x Signal LED 1x Limiter LED 1x Frontal LED 1x Button and 1x LED System Test
Housing	Wooden Cabinet
Handles	3 (1x side, 1 on top)
Rigging Points	12x M10 Thread
Pole mount	D36mm
Width	420 mm (16.5 in)
Height	820 mm (32.3 in)
Depth	520 mm (20.5 in)
Weight	39.5 kg (87.1 lbs)