

	FILTERS				NOTE
	TYPE	FREQ (Hz)	GAIN (dB)	Q	
IS4T	HPF 24dB/oct	110	-	-	
	LPF 24dB/oct	18000	-	-	
	Q-BELL	240	-4,5	1	
	Q-BELL	850	-3,5	2	
	Q-BELL	1600	-6	3	
	Q-BELL	3500	-8	1	
	Q-BELL	8700	-3	4	
	Q-BELL	12700	-8	2	
	SHELF	400	-7	1,141	
IS5T	HPF 24dB/oct	95	-	-	
	LPF 24dB/oct	20000	-	-	
	Q-BELL	200	-3,5	3	
	Q-BELL	890	-3,5	3	
	Q-BELL	1700	-5,5	3,5	
	Q-BELL	6300	-5	3	
	Q-BELL	11000	-3	2	
	SHELF	500	-11	1,141	
IS25T	HPF 24dB/oct	85	-	-	
	LPF 24dB/oct	18000	-	-	
	Q-BELL	230	-6	2	
	Q-BELL	450	-6	2,5	
	Q-BELL	1160	-6,5	5	
	Q-BELL	1900	-4	4	
	Q-BELL	2600	3,5	5	
	Q-BELL	4000	-2	2,5	
	SHELF	1600	-6	1,141	
IS26T	HPF 24dB/oct	80	-	-	
	LPF 24dB/oct	18000	-	-	
	Q-BELL	225	-5,5	2	
	Q-BELL	440	-3	4	
	Q-BELL	980	-4,5	4	
	Q-BELL	3800	-8	4	
	SHELF	1000	-3,5	1,141	
IS26T100	HPF 24dB/oct	80	-	-	
	LPF 24dB/oct	18000	-	-	
	Q-BELL	135	-9	4,3	
	Q-BELL	235	-8,5	3,5	
	Q-BELL	420	-6	5	
	Q-BELL	650	-3	6,5	
	Q-BELL	1000	-5,5	3,5	
	Q-BELL	1800	-3,5	4,5	
	Q-BELL	2500	10,5	4	
	Q-BELL	3200	-18,5	7,5	
	Q-BELL	11250	-6,5	6,5	
	SHELF	1500	notes	1,141	+2dB up to 4 boxes, +4dB from 4 to 6 boxes
IS8S	HPF 24dB/oct	50	-	-	
	LPF 24dB/oct	110	-	-	150 Hz PER COUPLING CON IS4T-IS5T
	Q-BELL	70	-1,5	4	
	Q-BELL	200	-12	3	
	Q-BELL	790	-8	2	
	Q-BELL	3300	-14	3	
IS12S	HPF 24dB/oct	40	-	-	
	LPF 24dB/oct	110	-	-	150 Hz PER COUPLING CON IS4T-IS5T
	Q-BELL	70	-1	4	
	Q-BELL	200	-15	3	
	Q-BELL	340	-10	2	
	Q-BELL	630	-5	4	
	Q-BELL	1600	-6	2	